



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Kelp Forest
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIFFE	Liv All Condition
VORBAU	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATTELSTÜTZE	Giant D-Fuse, composite, 14mm offset
SATTEL	Liv Approach
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-610, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSSEN	Shimano GRX BR-RX400 HRD, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-610 hydraulic
KASSETTE	Shimano CS-HG710, 12-speed, 11x36
KETTE	KMC X12L-1
KURBEL	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
TRETLAGER	FSA BB-AL86, press fit

LAUFRÄDER	
FELGEN	Giant P-X2 Disc, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Crosscut Grip, 700x40c, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sitzrohrlänge (mm)	390	420	465	500
Sitzrohrwinkel	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°
Oberrohrlänge (mm)	525 525	535 535	545 545	555 555
Steuerrohr-Länge (mm)	90	110	140	160
Steuerrohr-Winkel	70.0° 69.9°	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°
Gabelneigung (mm)	50	50	50	50
Trail (mm)	78.4 82	75 78.5	71.6 75.1	71.6 75
Radstand (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Kettenstreben-Länge (mm)	425 435	425 435	425 435	430 440
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Überstandshöhe (mm)	681 688	708 715	748 755	779 786
Lenkerbreite (mm)	400	400	420	420
Vorbaulänge (mm)	50	60	70	80
Kurbellänge (mm)	165	170	172.5	172.5
Radgrösse	700	700	700	700

Spezifikations-, Preis- und Farbänderungen vorbehalten.