DEVOTE ADVANCED 2



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Lunar Eclipse
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIFFE	Liv All Condition
VORBAU	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATTELSTÜTZE	Giant D-Fuse, composite, 14mm offset
SATTEL	Liv Grit
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-610, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSEN	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-610 hydraulic
KASSETTE	Shimano CS-HG710, 12-speed, 11x36
KETTE	KMC X12L-1
KURBEL	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant P-X2 Disc, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Sitzrohrlänge (mm)	390	420	465	500
Sitzrohrwinkel	74.5° | 74.4°	74.5° | 74.4°	74.5° | 74.4°	74.5° | 74.4°
Oberrohrlänge (mm)	525 | 525	535 | 535	545 | 545	555 | 555
Steuerrohr-Länge (mm)	90	110	140	160
Steuerrohr-Winkel	70.0° | 69.9°	70.5° | 70.4°	71.0° | 70.9°	71.0° | 70.9°
Gabelneigung (mm)	50	50	50	50
Trail (mm)	78.4 | 82	75 | 78.5	71.6 | 75.1	71.6 | 75
Radstand (mm)	1012 | 1022	1019 | 1029	1026 | 1036	1043 | 1052
Kettenstreben-Länge (mm)	425 | 435	425 | 435	425 | 435	430 | 440
Tretlager-Höhe (mm)	80 | 81	80 | 81	80 | 81	80 | 81
Stack (mm)	523 | 524	544 | 545	574 | 575	593 | 594
Reach (mm)	380 | 379	384 | 383	386 | 385	391 | 389
Überstandshöhe (mm)	681 | 688	708 | 715	748 | 755	779 | 786
Lenkerbreite (mm)	400	400	420	420
Vorbaulänge (mm)	50	60	70	80
Kurbellänge (mm)	165	170	172.5	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.