DEVOTE ADVANCED 2



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Kelp Forest
CUADRO	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
TIJERA	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
POTENCIA	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
POSTE DE ASIENTO	Giant Contact D-Fuse, composite, 14mm offset
ASIENTO	Liv Approach
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano GRX RX-610, 2x12
DESVIADOR	Shimano GRX RX-820
CAMBIO TRASERO	Shimano GRX RX-820
FRENOS	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x36
CADENA	KMC X12L-1
MULTIPLICACIÓN	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
EJE DE CENTRO	FSA, press fit

RUEDAS	
RUEDAS	Giant P-X2 Disc wheelset, alloy
MAZAS	Giant alloy, 12mm thru-axle
RAYOS	Sapim
NEUMÁTICOS	Maxxis Rambler, 700x40c, tubeless
EXTRAS	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

Precio: $62,990.00

GEOMETRÍA

CUADRO	XS	S	M
	SHORT | LONG	SHORT | LONG	SHORT | LONG
Longitud de la Base del Poste de Asiento (mm)	390	420	465
Ángulo de la Base del Poste de Asiento	74.5° | 74.4°	74.5° | 74.4°	74.5° | 74.4°
Longitud del Tubo Superior (mm)	525 | 525	535 | 535	545 | 545
Longitud del Telescopio (mm)	90	110	140
Ángulo del Telescopio	70.0° | 69.9°	70.5° | 70.4°	71.0° | 70.9°
Rake (mm)	50	50	50
Trail (mm)	78.4 | 82	75 | 78.5	71.6 | 75.1
Distancia entre Ejes (mm)	1012 | 1022	1019 | 1029	1026 | 1036
Longitud de Vaina Inferior (mm)	425 | 435	425 | 435	425 | 435
Caída del Eje de Centro (mm)	80 | 81	80 | 81	80 | 81
Stack (mm)	523 | 524	544 | 545	574 | 575
Reach (mm)	380 | 379	384 | 383	386 | 385
Altura del Tubo Superior al Suelo (mm)	681 | 688	708 | 715	748 | 755
Ancho del Manubrio (mm)	400	400	420
Longitud de la Potencia (mm)	50	60	70
Longitud de la Biela (mm)	165	170	172.5
Tamaño de las Ruedas	700	700	700

Todas las especificaciones están sujetas a cambios sin previo aviso.