

DEVOTE ADVANCED 2



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Lunar Eclipse
RUNKO	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
HAARUKKA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
ISKUNVAIMENNIN	N/A
KOMPONENTIT	
OHJAUSTANKO	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPIT	Liv All Condition
OHJAINKANNATIN	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATULATOLPPA	Giant D-Fuse, composite, 14mm offset
SATULA	Liv Grit
VOIMANSIIRTO	
VAIHDEVIPU	Shimano GRX RX-610, 2x12
ETUVAIHTAJA	Shimano GRX RX-820
TAKAVAIHTAJA	Shimano GRX RX-820
JARRUT	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
JARRUKAIVAT	Shimano GRX RX-610 hydraulic
RATASPAKKA	Shimano CS-HG710, 12-speed, 11x36
KETJUT	KMC X12L-1
KAMPISARJA	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant P-X2 Disc, alloy
NAVAT	Giant alloy, 12mm thru-axle
PINNAT	Sapim
RENKAAT	Giant Crosscut Grip, 700x45c, tubeless
LISÄTIEDOT	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
RAJOITTEET	
MAX RENGASVARA	53mm

Suositusuhinta: 3 199,00 €

GEOMETRIA

RUNKO	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Satulaputken pituus (mm)	390	420	465	500
Satulaputken kulma	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Vaakaputken pituus (mm)	525 525	535 535	545 545	555 555
Emäputken pituus (mm)	90	110	140	160
Emäputken kulma	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Haarukan offset (mm)	50	50	50	50
Trail-mitta (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Akseliväli (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Takahaarukan alaputken pituus (mm)	425 435	425 435	425 435	430 440
Keskiön pudotus (mm)	80 81	80 81	80 81	80 81
Stack-mitta (mm)	523 524	544 545	574 575	593 594
Reach-mitta (mm)	380 379	384 383	386 385	391 389
Standover-mitta (mm)	681 688	708 715	748 755	779 786
Ohjaustangon leveys (mm)	400	400	420	420
Ohjainkannattimen pituus (mm)	50	60	70	80
Kammen pituus (mm)	165	170	172,5	172,5

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.