

DEVOTE ADVANCED 2



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Lunar Eclipse
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELPEN	Giant D-Fuse, composite, 14mm offset
ZADEL	Liv Grit
AFMONTAGE	
SHIFTERS	Shimano GRX RX-610, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant P-X2 Disc, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Crosscut Grip, 700x45c, tubeless
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAXIMALE BANDENVRIJHEID	53mm

Adviesprijs: € 2.999,00

GEOMETRIE

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Zitbuis Lengte (mm)	390		420		465		500	
Zitbuis Hoek	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°
Frame Lengte (horizontaal) (mm)	525	525	535	535	545	545	555	555
Balhoofdbuis Lengte (mm)	90		110		140		160	
Balhoofdbuis Hoek	70,0°	69,9°	70,5°	70,4°	71,0°	70,9°	71,0°	70,9°
Vork Sprong (mm)	50		50		50		50	
Naloop (mm)	78,4	82	75	78,5	71,6	75,1	71,6	75
Wielbasis (mm)	1012	1022	1019	1029	1026	1036	1043	1052
Liggende achtervork lengte (mm)	425	435	425	435	425	435	430	440
Bottom Bracket Drop (mm)	80	81	80	81	80	81	80	81
Stack (mm)	523	524	544	545	574	575	593	594
Reach (mm)	380	379	384	383	386	385	391	389
Stand Over Height (mm)	681	688	708	715	748	755	779	786
Stuur breedte (mm)	400		400		420		420	
Stuurpen Lengte (mm)	50		60		70		80	
Cranklengte (mm)	165		170		172,5		172,5	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.