

DEVOTE ADVANCED 2



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Kelp Forest
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELPEN	Giant D-Fuse, composite, 14mm offset
ZADEL	Liv Approach
AFMONTAGE	
SHIFTERS	Shimano GRX RX-610, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX BR-RX400 HRD, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
AANDRIJVING	KMC X12L-1
CRANKSET	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	FSA BB-AL86, press fit

WIELSET	
VELGEN	Giant P-X2 Disc, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Crosscut Grip, 700x40c, tubeless
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

Adviesprijs: € 2.999,00

GEOMETRIE

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Zitbuis Lengte (mm)	390		420		465		500	
Zitbuis Hoek	74,5° 74,4°		74,5° 74,4°		74,5° 74,4°		74,5° 74,4°	
Frame Lengte (horizontaal) (mm)	525 525		535 535		545 545		555 555	
Balhoofdbuis Lengte (mm)	90		110		140		160	
Balhoofdbuis Hoek	70,0° 69,9°		70,5° 70,4°		71,0° 70,9°		71,0° 70,9°	
Vork Sprong (mm)	50		50		50		50	
Naloop (mm)	78,4 82		75 78,5		71,6 75,1		71,6 75	
Wielbasis (mm)	1012 1022		1019 1029		1026 1036		1043 1052	
Liggende achtervork lengte (mm)	425 435		425 435		425 435		430 440	
Bottom Bracket Drop (mm)	80 81		80 81		80 81		80 81	
Stack (mm)	523 524		544 545		574 575		593 594	
Reach (mm)	380 379		384 383		386 385		391 389	
Stand Over Height (mm)	681 688		708 715		748 755		779 786	
Stuur breedte (mm)	400		400		420		420	
Stuurpen Lengte (mm)	50		60		70		80	
Cranklengte (mm)	165		170		172,5		172,5	
Wielmaat	700		700		700		700	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.