

# DEVOTE ADVANCED 2



## SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Lunar Eclipse
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELLEN	Giant D-Fuse, composite, 14mm offset
ZADEL	Liv Grit
AFMONTAGE	
SHIFTERS	Shimano GRX RX-610, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant P-X2 Disc, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Crosscut Grip, 700x45c, tubeless
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAXIMALE BANDENVRIJHEID	53mm

Adviesprijs: € 2.999,00

## GEOMETRIE

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Zitbuis Lengte (mm)	390	420	465	500				
Zitbuis Hoek	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°				
Frame Lengte (horizontaal) (mm)	525   525	535   535	545   545	555   555				
Balhoofdbuis Lengte (mm)	90	110	140	160				
Balhoofdbuis Hoek	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°				
Vork Sprong (mm)	50	50	50	50				
Naloop (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75				
Wielbasis (mm)	1012   1022	1019   1029	1026   1036	1043   1052				
Liggende achtervork lengte (mm)	425   435	425   435	425   435	430   440				
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Stand Over Height (mm)	681   688	708   715	748   755	779   786				
Stuur breedte (mm)	400	400	420	420				
Stuurpen Lengte (mm)	50	60	70	80				
Cranklengte (mm)	165	170	172,5	172,5				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.