# DEVOTE ADVANCED 2



## SPECS

| RAMME | |
|---|---|
| **STØRRELSE** | XS, S, M, L |
| **FARGE** | Kelp Forest |
| **RAMME** | Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing |
| **GAFFEL** | Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc |
| **DEMPER** | N/A |
| **KOMPONENTER** | |
| **STYRE** | Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| **GRIPS** | Liv All Condition |
| **STYRSTEM** | Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm |
| **SETEPINNE** | Giant Contact D-Fuse, composite, 14mm offset |
| **SADEL** | Liv Approach |
| **PEDALER** | N/A |
| **DRIVVERK** | |
| **GIRHENDLER** | Shimano GRX RX-610, 2x12 |
| **FRONTGIR** | Shimano GRX RX-820 |
| **BAKGIR** | Shimano GRX RX-820 |
| **BREMSER** | Shimano GRX BR-RX410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm |
| **BREMSEHENDLER** | Shimano GRX RX-610 hydraulic |
| **KASSETT** | Shimano 105, 12-speed, 11x36 |
| **KJEDE** | KMC X12L-1 |
| **KRANK** | FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm |
| **BOTTOM BRACKET** | FSA, press fit |

| HJUL | |
|---|---|
| **FELG** | Giant P-X2 Disc wheelset, alloy |
| **NAV** | Giant alloy, 12mm thru-axle |
| **EIKE** | Sapim |
| **DEKK** | Maxxis Rambler, 700x40c, tubeless |
| **EXTRAS** | 53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag |

## GEOMETRI

| RAMME | XS | S | M | L |
|---|---|---|---|---|
| | SHORT \| LONG | SHORT \| LONG | SHORT \| LONG | SHORT \| LONG |
| Seat Tube Length (mm) | 390 | 420 | 465 | 500 |
| Seat Tube Angle | 74,5° \| 74,4° | 74,5° \| 74,4° | 74,5° \| 74,4° | 74,5° \| 74,4° |
| Top Tube Length (mm) | 525 \| 525 | 535 \| 535 | 545 \| 545 | 555 \| 555 |
| Head Tube Length (mm) | 90 | 110 | 140 | 160 |
| Head Tube Angle | 70,0° \| 69,9° | 70,5° \| 70,4° | 71,0° \| 70,9° | 71,0° \| 70,9° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 |
| Trail (mm) | 78,4 \| 82 | 75 \| 78,5 | 71,6 \| 75,1 | 71,6 \| 75 |
| Wheelbase (mm) | 1012 \| 1022 | 1019 \| 1029 | 1026 \| 1036 | 1043 \| 1052 |
| Chain Stay Length (mm) | 425 \| 435 | 425 \| 435 | 425 \| 435 | 430 \| 440 |
| Bottom Bracket Drop (mm) | 80 \| 81 | 80 \| 81 | 80 \| 81 | 80 \| 81 |
| Stack (mm) | 523 \| 524 | 544 \| 545 | 574 \| 575 | 593 \| 594 |
| Reach (mm) | 380 \| 379 | 384 \| 383 | 386 \| 385 | 391 \| 389 |
| Stand Over Height (mm) | 681 \| 688 | 708 \| 715 | 748 \| 755 | 779 \| 786 |
| Handlebar Width (mm) | 400 | 400 | 420 | 420 |
| Stem Length (mm) | 50 | 60 | 70 | 80 |
| Crank Length (mm) | 165 | 170 | 172,5 | 172,5 |
| Wheel Size | 700 | 700 | 700 | 700 |

*Alle spesifikasjonene kan endres uten varsel.*