

DEVOTE ADVANCED 2



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Kelp Forest
RAMME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STYRSTEM	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SETEPINNE	Giant D-Fuse, composite, 14mm offset
SADEL	Liv Approach
DRIVVERK	
GIRHENDLER	Shimano GRX RX-610, 2x12
FRONTGIR	Shimano GRX RX-820
BAKGIR	Shimano GRX RX-820
BREMSE	Shimano GRX BR-RX400 HRD, Giant MPH rotors [F]160mm, [R]160mm
BREMSEHENDLER	Shimano GRX RX-610 hydraulic
KASSETT	Shimano CS-HG710, 12-speed, 11x36
KJEDE	KMC X12L-1
KRANK	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	FSA BB-AL86, press fit

HJUL	
FELG	Giant P-X2 Disc, alloy
NAV	Giant alloy, 12mm thru-axle
EIKE	Sapim
DEKK	Giant Crosscut Grip, 700x40c, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

GEOMETRI

RAMME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°				
Top Tube Length (mm)	525 525	535 535	545 545	555 555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052				
Chain Stay Length (mm)	425 435	425 435	425 435	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172,5	172,5				
Wheel Size	700	700	700	700				

Alle spesifikasjonene kan endres uten varsel.