

# DEVOTE ADVANCED 2



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLORS</b>	Kelp Forest
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
<b>FORK</b>	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
<b>GRIPS</b>	Liv All Condition
<b>STEM</b>	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
<b>SEATPOST</b>	Giant D-Fuse, composite, 14mm offset
<b>SADDLE</b>	Liv Approach
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano GRX RX-610, 2x12
<b>FRONT DERAILLEUR</b>	Shimano GRX RX-820
<b>REAR DERAILLEUR</b>	Shimano GRX RX-820
<b>BRAKES</b>	Shimano GRX BR-RX400 HRD, Giant MPH rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano GRX RX-610 hydraulic
<b>CASSETTE</b>	Shimano CS-HG710, 12-speed, 11x36
<b>CHAIN</b>	KMC X12L-1
<b>CRANKSET</b>	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
<b>BOTTOM BRACKET</b>	FSA BB-AL86, press fit

WHEELS	
<b>RIMS</b>	Giant P-X2 Disc, alloy
<b>HUBS</b>	Giant alloy, 12mm thru-axle
<b>SPOKES</b>	Sapim
<b>TIRES</b>	Giant Crosscut Grip, 700x40c, tubeless
<b>EXTRAS</b>	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

## GEOMETRY

FRAME	XS	S	M	L
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Top Tube Length (mm)	525   525	535   535	545   545	555   555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Wheelbase (mm)	1012   1022	1019   1029	1026   1036	1043   1052
Chain Stay Length (mm)	425   435	425   435	425   435	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81
Stack (mm)	523   524	544   545	574   575	593   594
Reach (mm)	380   379	384   383	386   385	391   389
Stand Over Height (mm)	681   688	708   715	748   755	779   786
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	50	60	70	80
Crank Length (mm)	165	170	172,5	172,5
Wheel Size	700	700	700	700

All specifications listed are subject to change without notice.