

DEVOTE ADVANCED 2



SPECS

CADRU	
MARIMI	XS, S, M, L
CULORI	Kelp Forest
CADRU	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
FURCA	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
SOC	N/A
COMPONENTE	
GHIDON	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
PIPA	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
TIJA SA	Giant Contact D-Fuse, composite, 14mm offset
SA	Liv Approach
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano GRX RX-610, 2x12
SCHIMBATOR FATA	Shimano GRX RX-820
SCHIMBATOR SPATE	Shimano GRX RX-820
FRANE	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
MANETE FRANA	Shimano GRX RX-610 hydraulic
PINIOANE	Shimano 105, 12-speed, 11x36
LANT	KMC X12L-1
ANGRENAJ	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	FSA, press fit

ROTI	
JANTE	Giant P-X2 Disc wheelset, alloy
BUTUCI	Giant alloy, 12mm thru-axle
SPITE	Sapim
ANVELOPE	Maxxis Rambler, 700x40c, tubeless
EXTRAS	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

GEOMETRIE

CADRU	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°				
Top Tube Length (mm)	525 525	535 535	545 545	555 555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052				
Chain Stay Length (mm)	425 435	425 435	425 435	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172,5	172,5				
Wheel Size	700	700	700	700				

Toate specificatiile enumerate se pot schimba fara notificare prealabila.