DEVOTE ADVANCED 2



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Kelp Forest
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
VILICE	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
OPORA KRMILA	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
OPORA SEDEŽA	Giant Contact D-Fuse, composite, 14mm offset
SEDEŽ	Liv Approach
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano GRX RX-610, 2x12
PREDNJI MENJALNIK	Shimano GRX RX-820
ZADNJI MENJALNIK	Shimano GRX RX-820
ZAVORE	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano GRX RX-610 hydraulic
VERIŽNIK	Shimano 105, 12-speed, 11x36
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	FSA, press fit

OBROČNIKI	
OBROČI	Giant P-X2 Disc wheelset, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Maxxis Rambler, 700x40c, tubeless
DODATKI	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

GEOMETRIJA

OKVIR	XS	S	M	L
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Dolžina sedežne cevi (mm)	390	420	465	500
Kot sedežne cevi	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°
Top Tube Length (mm)	525 | 525	535 | 535	545 | 545	555 | 555
Višina glave okvirja (mm)	90	110	140	160
Krmilni kot	70,0° | 69,9°	70,5° | 70,4°	71,0° | 70,9°	71,0° | 70,9°
Zamik vpetja osi (mm)	50	50	50	50
Trail (mm)	78,4 | 82	75 | 78,5	71,6 | 75,1	71,6 | 75
Medosna razdalja (mm)	1012 | 1022	1019 | 1029	1026 | 1036	1043 | 1052
Dolžina cevi ob verigi (mm)	425 | 435	425 | 435	425 | 435	430 | 440
Bottom Bracket Drop (mm)	80 | 81	80 | 81	80 | 81	80 | 81
Oddaljenost zgornje cevi od gonilne osi (mm)	523 | 524	544 | 545	574 | 575	593 | 594
Doseg (mm)	380 | 379	384 | 383	386 | 385	391 | 389
Višina zgornje cevi (mm)	681 | 688	708 | 715	748 | 755	779 | 786
Širina krmila (mm)	400	400	420	420
Dolžina opore krmila (mm)	50	60	70	80
Dolžina gonilke (mm)	165	170	172,5	172,5
Velikost obročnikov	700	700	700	700

Vse navedene specifikacije se lahko spremenijo brez obvestila.