

DEVOTE ADVANCED 2



SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Kelp Forest
RAM	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GREPPAR	Liv All Condition
STAM	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SADELSTOLPE	Giant D-Fuse, composite, 14mm offset
SADEL	Liv Approach
DRIVLINAN	
VÄXLAR	Shimano GRX RX-610, 2x12
FRAMVÄXEL	Shimano GRX RX-820
BAKVÄXEL	Shimano GRX RX-820
BROMSAR	Shimano GRX BR-RX400 HRD, Giant MPH rotors [F]160mm, [R]160mm
BROMSSPAKAR	Shimano GRX RX-610 hydraulic
KASSETT	Shimano CS-HG710, 12-speed, 11x36
KEDJA	KMC X12L-1
VEVPARTI	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BROMSREGLAGE	FSA BB-AL86, press fit

HJUL	
FÄLGAR	Giant P-X2 Disc, alloy
NAV	Giant alloy, 12mm thru-axle
EKRAR	Sapim
DÄCK	Giant Crosscut Grip, 700x40c, tubeless
EXTRAFUNKTIONER	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

Price: 35 290,00 kr

GEOMETRY

RAM	S	L
Längd sadelrör (mm)	SHORT LONG	SHORT LONG
Vinkel sadelrör	74,5° 74,4°	74,5° 74,4°
Topprörets längd (mm)	535 535	555 555
Styrhuvud Längd (mm)	110	160
Vinkel styrhuvud	70,5° 70,4°	71,0° 70,9°
Gaffelvinkel (mm)	50	50
Spår (mm)	75 78,5	71,6 75
Hjulbas (mm)	1019 1029	1043 1052
Kedjestagslängd (mm)	425 435	430 440
Nedre fäste Drop (mm)	80 81	80 81
Stack (mm)	544 545	593 594
Reach (mm)	384 383	391 389
Stå över höjden (mm)	708 715	779 786
Styrets bredd (mm)	400	420
Stamlängd (mm)	60	80
Vevlängd (mm)	170	172,5
Hjulstorlek	700	700

All specifications listed are subject to change without notice.