

DEVOTE ADVANCED PRO



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, L
ЦВЯТ	Carbon/Chrome
РАМКА	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
ВИЛКА	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
ЗАДЕН АМОРТИСЬОР	N/A
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
ГРИПОВЕ	Liv All Condition
ЛАПА	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
СЕДАЛКА	Liv Approach SL
ПЕДАЛИ	N/A
DRIVETRAIN	
КОМАНДИ	SRAM Force eTap AXS, 2x12
ПРЕДЕН ДЕРАЙЛЪОР	SRAM Force eTap AXS Wide
ЗАДЕН ДЕРАЙЛЪОР	SRAM Force eTap AXS
СПИРАЧКИ	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	SRAM Force eTap AXS hydraulic
КАСЕТА	SRAM Force, 12-speed, 10x36
ВЕРИГА	SRAM Force D2
КУРБЕЛ	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
ГЛАВИНИ	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
СПИЦИ	Sapim CX-Ray
ГУМИ	CADEX AR, 700x40c, tubeless
ЕКСТРИ	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

ГЕОМЕТРИЯ

РАМКА	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Top Tube Length (mm)	525 525	535 535	545 545	555 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Chain Stay Length (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Обсер (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Ширина на Кормило (mm)	400	400	420	420
Дължина на Лапа (mm)	50	60	70	80
Дължина на Курбел (mm)	165	170	172,5	172,5
Размер на Каплите	700	700	700	700

All specifications listed are subject to change without notice.