

DEVOTE ADVANCED PRO



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Nebula/Chrome
RAMME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
FORGAFFEL	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
BAGDÆMPER	N/A
KOMPONENTER	
STYR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GREB / STYRBÅND	Liv All Condition
FREMPIND	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SADELPIND	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	Liv Grit SL
PEDALER	platform pedal [GCS, GTS], no pedal [All other GSC]
GEARGRUPPE	
SKIFTEGREB	SRAM Force AXS E1, 2x12
FORSKIFTER	SRAM Force AXS E1
BAGSKIFTER	SRAM Force AXS D2
BREMSE	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
BREMSEGREB	SRAM Force AXS E1 hydraulic
KASSETTE	SRAM Force E1, 12-speed, 10x36
KÆDE	SRAM Force E1
KRANKSÆT	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant CXR 1, [F] 35mm, [R] 35mm
NAV	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
EGER	Sapim CX-Ray
DÆK	CADEX GX, 700x40c, foldable, tubeless
EKSTRA	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
GRÆNSER	
MAX DÆKSTØRRELSE	53mm

Pris: 53.299,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørlængde (mm)	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sadelrørsvinkel	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Overrørsrørlængde (mm)	525 525	535 535	545 545	555 555
Kronrørlængde (mm)	90	110	140	160
Kronrørsvinkel	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Forgaffel fremspring (rake) (mm)	50	50	50	50
Sti (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Akselafstand (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Kædestagslængde (mm)	425 435	425 435	425 435	430 440
Krankboks drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Skridthøjde (mm)	681 688	708 715	748 755	779 786
Styrbredde (mm)	400	400	420	420
Frempindslængde (mm)	50	60	70	80
Pedalarmslængde (mm)	165	170	172,5	172,5

Alle de anførte specifikationer kan ændres uden varsel.