

DEVOTE ADVANCED PRO



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, L
ΧΡΩΜΑΤΑ	Carbon/Chrome
ΣΚΕΛΕΤΟΣ	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
ΠΙΡΟΥΝΙ	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
ΑΝΑΡΤΗΣΗ	N/A
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ΛΑΙΜΟΣ Σ'ΕΛΛΑΣ	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
Σ'ΕΛΛΑ	Liv Approach SL
ΠΕΝΤ'ΑΛ	N/A
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM Force eTap AXS, 2x12
ΝΤΕΡΑΓ'ΕΡ ΕΜΠΡΟΣΘΙΟ	SRAM Force eTap AXS Wide
ΝΤΕΡΑΓ'ΕΡ ΟΠΙΣΘΙΟ	SRAM Force eTap AXS
ΦΡΕΝΑ	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
ΜΑΝ'ΕΤΤΕΣ ΦΡΕΝΩΝ	SRAM Force eTap AXS hydraulic
CASETTE Ή ΕΛΕΥΘΕΡΟ	SRAM Force, 12-speed, 10x36
ΑΛΥΣΙΔΑ	SRAM Force D2
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
ΚΕΝΤΡΑ	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
ΑΚΤΙΝΕΣ	Sapim CX-Ray
ΕΛΑΣΤΙΚΑ	CADEX AR, 700x40c, tubeless
EXTRAS	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Top Tube Length (mm)	525 525	535 535	545 545	555 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Chain Stay Length (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	50	60	70	80
Crank Length (mm)	165	170	172,5	172,5
Wheel Size	700	700	700	700

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση