

DEVOTE ADVANCED PRO



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Carbon/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
FORK	Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
SADDLE	Liv Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS, 2x12
FRONT DERAILLEUR	SRAM Force eTap AXS Wide
REAR DERAILLEUR	SRAM Force eTap AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x36
CHAIN	SRAM Force D1
CRANKSET	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX AR, 700x40c, tubeless
EXTRAS	53mm max tyre size in long flip chip position, 45mm max tyre size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

Price: \$8,299.00

GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°				
Top Tube Length (mm)	525 525	535 535	545 545	555 555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70.0° 69.9°	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78.4 82	75 78.5	71.6 75.1	71.6 75				
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052				
Chain Stay Length (mm)	425 435	425 435	425 435	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172.5	172.5				
Wheel Size	700	700	700	700				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.