

DEVOTE ADVANCED PRO



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Nebula/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Liv Grit SL
PEDALS	platform pedal [GCS, GTS], no pedal [All other GSC]
DRIVETRAIN	
SHIFTERS	SRAM Force AXS E1, 2x12
FRONT DERAILLEUR	SRAM Force AXS E1
REAR DERAILLEUR	SRAM Force AXS D2
BRAKES	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force AXS E1 hydraulic
CASSETTE	SRAM Force E1, 12-speed, 10x36
CHAIN	SRAM Force E1
CRANKSET	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1, [F] 35mm, [R] 35mm
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX GX, 700x40c, foldable, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Suggested Retail Price (CDN): \$7,699.00

FRAME GEOMETRY

FRAME	XS	S	M
	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	390	420	465
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°
Top Tube Length (mm)	525 525	535 535	545 545
Head Tube Length (mm)	90	110	140
Head Tube Angle	70.0° 69.9°	70.5° 70.4°	71.0° 70.9°
Fork Rake (mm)	50	50	50
Trail (mm)	78.4 82	75 78.5	71.6 75.1
Wheelbase (mm)	1012 1022	1019 1029	1026 1036
Chain Stay Length (mm)	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575
Reach (mm)	380 379	384 383	386 385
Stand Over Height (mm)	681 688	708 715	748 755
Handlebar Width (mm)	400	400	420
Stem Length (mm)	50	60	70
Crank Length (mm)	165	170	172.5

All prices and specifications are subject to change without notice.