

DEVOTE ADVANCED PRO



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Carbon/Gold Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm
SEATPOST	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
SADDLE	Liv Approach SL
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS, 2x12
FRONT DERAILLEUR	SRAM Force eTap AXS Wide
REAR DERAILLEUR	SRAM Force eTap AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x36
CHAIN	SRAM Force D2
CRANKSET	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TYRES	CADEX AR, 700x40c, tubeless
EXTRAS	factory tubeless set up, ISC clamp, integrated down tube storage bag
LIMITS	
MAX TYRE CLEARANCE	53mm max tyre size in long flip chip position, 45mm max tyre size in short flip chip position
MAX CHAINRING SIZE	SRAM Wide 2x 43-30, 1x 44T. Shimano GRX 2x 48-31, 1x 42T

Price: £5,599.00

GEOMETRY

FRAME	XS		S		M	
	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	420	465	465	465
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°
Top Tube Length (mm)	525 525	535 535	545 545	545 545	545 545	545 545
Head Tube Length (mm)	90	110	110	140	140	140
Head Tube Angle	70.0° 69.9°	70.5° 70.4°	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°	71.0° 70.9°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78.4 82	75 78.5	75 78.5	71.6 75.1	71.6 75.1	71.6 75.1
Wheelbase (mm)	1012 1022	1019 1029	1019 1029	1026 1036	1026 1036	1026 1036
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	544 545	574 575	574 575	574 575
Reach (mm)	380 379	384 383	384 383	386 385	386 385	386 385
Stand Over Height (mm)	681 688	708 715	708 715	748 755	748 755	748 755
Handlebar Width (mm)	400	400	400	420	420	420
Stem Length (mm)	50	60	60	70	70	70
Crank Length (mm)	165	170	170	172.5	172.5	172.5
Wheel Size	700	700	700	700	700	700

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.