

DEVOTE ADVANCED PRO



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Carbon/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
SADDLE	Liv Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS, 2x12
FRONT DERAILLEUR	SRAM Force eTap AXS Wide
REAR DERAILLEUR	SRAM Force eTap AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x36
CHAIN	SRAM Force D2
CRANKSET	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX AR, 700x40c, tubeless
EXTRAS	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

Price: ₹ 6,999.00

GEOMETRY

FRAME	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	420	465	500
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°
Top Tube Length (mm)	535 535	545 545	555 555
Head Tube Length (mm)	110	140	160
Head Tube Angle	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°
Fork Rake (mm)	50	50	50
Trail (mm)	75 78.5	71.6 75.1	71.6 75
Wheelbase (mm)	1019 1029	1026 1036	1043 1052
Chain Stay Length (mm)	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81
Stack (mm)	544 545	574 575	593 594
Reach (mm)	384 383	386 385	391 389
Stand Over Height (mm)	708 715	748 755	779 786
Handlebar Width (mm)	400	420	420
Stem Length (mm)	60	70	80
Crank Length (mm)	170	172.5	172.5
Wheel Size	700	700	700

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.