

# DEVOTE ADVANCED PRO \*



## SPECS

| FRAME            |   |
|------------------|---|
| SIZES            | XS, S, M  |
| COLORS           | Nebula  |
| FRAME            | Advanced-Grade Composite, 12x142mm thru-axle, flat mount disc, flip chip dropout, integrated downtube storage |
| FORK             | Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc                           |
| SHOCK            | N/A   |
| COMPONENTS       |   |
| HANDLEBAR        | Giant Contact SLR XR D-Fuse, 31.8mm XS:40cm, S:40cm, M:42cm   |
| GRIPS            | Liv All Condition   |
| STEM             | Giant Contact Aerolight XS:50mm, S:60mm, M:70mm   |
| SEATPOST         | Giant D-Fuse SLR, composite, -5/+15mm offset  |
| SADDLE           | Liv Grit SL   |
| PEDALS           | N/A   |
| DRIVETRAIN       |   |
| SHIFTERS         | SRAM Force AXS HRD, ED-Force-E1   |
| FRONT DERAILLEUR | SRAM Force AXS Wide D2  |
| REAR DERAILLEUR  | SRAM Force AXS, RD-Force-E-E1   |
| BRAKES           | SRAM Force AXS HRD, ED-Force-E1, SRAM PaceLine X rotors [F]160mm, [R]160mm                                    |
| BRAKE LEVERS     | SRAM Force AXS HRD, ED-Force-E1   |
| CASSETTE         | SRAM Force E1 XG-1270, 12-speed, 10-36  |
| CHAIN            | SRAM Force-E1, 12-speed   |
| CRANKSET         | SRAM Force D2 Wide, DUB, 30/43 XS:165mm, S:170mm, M:172.5mm   |
| BOTTOM BRACKET   | SRAM DUB, press fit   |

| WHEELS             |  |
|--------------------|--|
| RIMS               | Giant CXR 1 Carbon Disc WheelSystem  |
| HUBS               | [F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle                    |
| SPOKES             | Sapim CX-Ray   |
| TIRES              | CADEX GX, 700x40c, tubeless  |
| EXTRAS             | Tubeless prepared, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position, in-frame storage bag |
| LIMITS             |  |
| MAX TIRE CLEARANCE | 53mm max tyre size in "long" flip chip position  |

**Price: \$9,499.00**

## GEOMETRY

| FRAME                    | XS            |               | S             |               | M     |      | L     |      |
|--------------------------|---------------|---------------|---------------|---------------|-------|------|-------|------|
|                          | SHORT         | LONG          | SHORT         | LONG          | SHORT | LONG | SHORT | LONG |
| Seat Tube Length (mm)    | 390           | 420           | 465           | 500           |       |      |       |      |
| Seat Tube Angle          | 74.5°   74.4° | 74.5°   74.4° | 74.5°   74.4° | 74.5°   74.4° |       |      |       |      |
| Top Tube Length (mm)     | 525   525     | 535   535     | 545   545     | 555   555     |       |      |       |      |
| Head Tube Length (mm)    | 90            | 110           | 140           | 160           |       |      |       |      |
| Head Tube Angle          | 70.0°   69.9° | 70.5°   70.4° | 71.0°   70.9° | 71.0°   70.9° |       |      |       |      |
| Fork Rake (mm)           | 50            | 50            | 50            | 50            |       |      |       |      |
| Trail (mm)               | 78.4   82     | 75   78.5     | 71.6   75.1   | 71.6   75     |       |      |       |      |
| Wheelbase (mm)           | 1012   1022   | 1019   1029   | 1026   1036   | 1043   1052   |       |      |       |      |
| Chain Stay Length (mm)   | 425   435     | 425   435     | 425   435     | 430   440     |       |      |       |      |
| Bottom Bracket Drop (mm) | 80   81       | 80   81       | 80   81       | 80   81       |       |      |       |      |
| Stack (mm)               | 523   524     | 544   545     | 574   575     | 593   594     |       |      |       |      |
| Reach (mm)               | 380   379     | 384   383     | 386   385     | 391   389     |       |      |       |      |
| Stand Over Height (mm)   | 681   688     | 708   715     | 748   755     | 779   786     |       |      |       |      |
| Stem Length (mm)         | 50            | 60            | 70            | 80            |       |      |       |      |
| Crank Length (mm)        | 165           | 170           | 172.5         | 172.5         |       |      |       |      |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.