

DEVOTE ADVANCED PRO



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Carbon/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
SADDLE	Liv Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS, 2x12
FRONT DERAILLEUR	SRAM Force eTap AXS Wide
REAR DERAILLEUR	SRAM Force eTap AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x36
CHAIN	SRAM Force D2
CRANKSET	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX AR, 700x40c, tubeless
EXTRAS	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

Recommended Retail Price: \$7,000.00

GEOMETRY

FRAME	S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (inch)	16.5	18.3	19.7			
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°			
Top Tube Length (inch)	21.1 21.1	21.5 21.5	21.9 21.9			
Head Tube Length (inch)	4.3	5.5	6.3			
Head Tube Angle	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°			
Fork Rake (inch)	2	2	2			
Trail (inch)	3 3.1	2.8 3	2.8 3			
Wheelbase (inch)	40.1 40.5	40.4 40.8	41.1 41.4			
Chain Stay Length (inch)	16.7 17.1	16.7 17.1	16.9 17.3			
Bottom Bracket Drop (inch)	3.1 3.2	3.1 3.2	3.1 3.2			
Stack (inch)	21.4 21.5	22.6 22.6	23.3 23.4			
Reach (inch)	15.1 15.1	15.2 15.2	15.4 15.3			
Stand Over Height (inch)	27.9 28.1	29.4 29.7	30.7 30.9			
Handlebar Width (inch)	15.7	16.5	16.5			
Stem Length (inch)	2.4	2.8	3.1			
Crank Length (inch)	6.7	6.8	6.8			
Wheel Size	700	700	700			

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*