

# DEVOTE ADVANCED PRO



## TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Carbon/Chrome
RUNKO	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
HAARUKKA	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
ISKUNVAIMENNIN	N/A
KOMPONENTIT	
OHJAUSTANKO	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPIT	Liv All Condition
OHJAINKANNATIN	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATULATOLPPA	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
SATULA	Liv Approach SL
POLKIMET	N/A
VOIMANSIIRTO	
VAIHDEVIIPU	SRAM Force eTap AXS, 2x12
ETUVAIHTAJA	SRAM Force eTap AXS Wide
TAKAVAIHTAJA	SRAM Force eTap AXS
JARRUT	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
JARRUKAHVAT	SRAM Force eTap AXS hydraulic
RATASPAKKA	SRAM Force, 12-speed, 10x36
KETJUT	SRAM Force D2
KAMPISARJA	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAVAT	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
PINNAT	Sapim CX-Ray
RENKAAT	CADEX AR, 700x40c, tubeless
LISÄTIEDOT	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

Suositus hinta: 7 259,00 €

## GEOMETRIA

RUNKO	L
	SHORT   LONG
Satulaputken pituus (mm)	500
Satulaputken kulma	74,5°   74,4°
Vaakaputken pituus (mm)	555   555
Emäputken pituus (mm)	160
Emäputken kulma	71,0°   70,9°
Haarukan offset (mm)	50
Trail-mitta (mm)	71,6   75
Akseliväli (mm)	1043   1052
Takahaarukan alaputken pituus (mm)	430   440
Keskion pudotus (mm)	80   81
Stack-mitta (mm)	593   594
Reach-mitta (mm)	391   389
Standover-mitta (mm)	779   786
Ohjaustangon leveys (mm)	420
Ohjainkannattimen pituus (mm)	80
Kammen pituus (mm)	172,5
Rengaskoko	700

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.