

DEVOTE ADVANCED PRO



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Ocean Twilight/Chrome
RUNKO	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
HAARUKKA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
ISKUNVAIMENNIN	N/A
KOMONENTIT	
OHJAUSTANKO	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPIT	Liv All Condition
OHJAINKANNATIN	Giant Contact AeroLight, -10 degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATULATOLPPA	Giant D-Fuse SLR, composite, -5/+15mm offset
SATULA	Liv Approach SL
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Force eTap AXS, 2x12
ETUVAIHTAJA	SRAM Force eTap AXS
TAKAVAIHTAJA	SRAM Force eTap AXS
JARRUT	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
JARRUKAHVAT	SRAM Force eTap AXS hydraulic
RATASPAKKA	SRAM Force, 12-speed, 10x36
KETJUT	SRAM Force D2
KAMPISARJA	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant CXR 1 Carbon Disc, [F] 35mm, [R] 35mm
NAVAT	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
PINNAT	Sapim CX-Ray
RENKAAT	CADEX GX, 700x40c, foldable, tubeless
LISÄTIEDOT	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

Suositusuhinta: 6 949,00 €

GEOMETRIA

RUNKO	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG
Satulaputken pituus (mm)	420	465	500
Satulaputken kulma	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Vaakaputken pituus (mm)	535 535	545 545	555 555
Emäputken pituus (mm)	110	140	160
Emäputken kulma	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Haarukan offset (mm)	50	50	50
Trail-mitta (mm)	75 78,5	71,6 75,1	71,6 75
Akseliväli (mm)	1019 1029	1026 1036	1043 1052
Takahaarukan alaputken pituus (mm)	425 435	425 435	430 440
Keskiön pudotus (mm)	80 81	80 81	80 81
Stack-mitta (mm)	544 545	574 575	593 594
Reach-mitta (mm)	384 383	386 385	391 389
Standover-mitta (mm)	708 715	748 755	779 786
Ohjaustangon leveys (mm)	400	420	420
Ohjainkannattimen pituus (mm)	60	70	80
Kammen pituus (mm)	170	172,5	172,5
Rengaskoko	700	700	700

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.