

DEVOTE ADVANCED PRO



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Nebula/Chrome
RUNKO	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
HAARUKKA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
ISKUNVAIMENNIN	N/A
KOMONENTIT	
OHJAUSTANKO	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPIT	Liv All Condition
OHJAINKANNATIN	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATULATOLPPA	Giant D-Fuse SLR, composite, -5/+15mm offset
SATULA	Liv Grit SL
POLKIMET	platform pedal [GCS, GTS], no pedal [All other GSC]
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Force AXS E1, 2x12
ETUVAIHTAJA	SRAM Force AXS E1
TAKAVAIHTAJA	SRAM Force AXS D2
JARRUT	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
JARRUKAHVAT	SRAM Force AXS E1 hydraulic
RATASPAKKA	SRAM Force E1, 12-speed, 10x36
KETJUT	SRAM Force E1
KAMPISARJA	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant CXR 1, [F] 35mm, [R] 35mm
NAVAT	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
PINNAT	Sapim CX-Ray
RENKAAT	CADEX GX, 700x40c, foldable, tubeless
LISÄTIEDOT	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
RAJOITTEET	
MAX RENGASVARA	53mm

Suositus hinta: 7 099,00 €

GEOMETRIA

RUNKO	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Satulaputken pituus (mm)	390	420	420	465	465	500	500	500
Satulaputken kulma	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Vaakaputken pituus (mm)	525 525	535 535	545 545	555 555	555 555	555 555	555 555	555 555
Emäputken pituus (mm)	90	110	110	140	140	160	160	160
Emäputken kulma	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°	71,0° 70,9°	71,0° 70,9°	71,0° 70,9°	71,0° 70,9°
Haarukan offset (mm)	50	50	50	50	50	50	50	50
Trail-mitta (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75	71,6 75	71,6 75	71,6 75	71,6 75
Akseliväli (mm)	1012 1022	1019 1029	1026 1036	1043 1052	1043 1052	1043 1052	1043 1052	1043 1052
Takahaarukan alaputken pituus (mm)	425 435	425 435	425 435	430 440	430 440	430 440	430 440	430 440
Keskiön pudotus (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Stack-mitta (mm)	523 524	544 545	574 575	593 594	593 594	593 594	593 594	593 594
Reach-mitta (mm)	380 379	384 383	386 385	391 389	391 389	391 389	391 389	391 389
Standover-mitta (mm)	681 688	708 715	748 755	779 786	779 786	779 786	779 786	779 786
Ohjaustangon leveys (mm)	400	400	420	420	420	420	420	420
Ohjainkannattimen pituus (mm)	50	60	70	80	80	80	80	80
Kammen pituus (mm)	165	170	172,5	172,5	172,5	172,5	172,5	172,5

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.