

# DEVOTE ADVANCED PRO



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Ocean Twilight/Chrome
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
<b>FORK</b>	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
<b>GRIPS</b>	Liv All Condition
<b>STEM</b>	Giant Contact AeroLight, -10 degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
<b>SEATPOST</b>	Giant D-Fuse SLR, composite, -5/+15mm offset
<b>SADDLE</b>	Liv Approach SL
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force eTap AXS, 2x12
<b>FRONT DERAILLEUR</b>	SRAM Force eTap AXS
<b>REAR DERAILLEUR</b>	SRAM Force eTap AXS
<b>BRAKES</b>	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force eTap AXS hydraulic
<b>CASSETTE</b>	SRAM Force, 12-speed, 10x36
<b>CHAIN</b>	SRAM Force D2
<b>CRANKSET</b>	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant CXR 1 Carbon Disc, [F] 35mm, [R] 35mm
<b>HUBS</b>	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim CX-Ray
<b>TIRES</b>	CADEX GX, 700x40c, foldable, tubeless
<b>EXTRAS</b>	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

**Suggested Retail Price (CDN): \$7,299.00**

## FRAME GEOMETRY

FRAME	XS	S	M
	SHORT   LONG	SHORT   LONG	SHORT   LONG
Seat Tube Length (mm)	390	420	465
Seat Tube Angle	74.5°   74.4°	74.5°   74.4°	74.5°   74.4°
Top Tube Length (mm)	525   525	535   535	545   545
Head Tube Length (mm)	90	110	140
Head Tube Angle	70.0°   69.9°	70.5°   70.4°	71.0°   70.9°
Fork Rake (mm)	50	50	50
Trail (mm)	78.4   82	75   78.5	71.6   75.1
Wheelbase (mm)	1012   1022	1019   1029	1026   1036
Chain Stay Length (mm)	425   435	425   435	425   435
Bottom Bracket Drop (mm)	80   81	80   81	80   81
Stack (mm)	523   524	544   545	574   575
Reach (mm)	380   379	384   383	386   385
Stand Over Height (mm)	681   688	708   715	748   755
Handlebar Width (mm)	400	400	420
Stem Length (mm)	50	60	70
Crank Length (mm)	165	170	172.5
Wheel Size	700	700	700

*All prices and specifications are subject to change without notice.*