

DEVOTE ADVANCED PRO



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Nebula/Chrome
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
GABEL	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIFFE	Liv All Condition
VORBAU	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATTELSTÜTZE	Giant D-Fuse SLR, composite, -5/+15mm offset
SATTEL	Liv Grit SL
PEDALE	platform pedal [GCS, GTS], no pedal [All other GSC]
ANTRIEB	
SCHALTHEBEL	SRAM Force AXS E1, 2x12
UMWERFER	SRAM Force AXS E1
SCHALTWERK	SRAM Force AXS D2
BREMSEN	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
BREMSHEBEL	SRAM Force AXS E1 hydraulic
KASSETTE	SRAM Force E1, 12-speed, 10x36
KETTE	SRAM Force E1
KURBEL	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant CXR 1, [F] 35mm, [R] 35mm
NABE	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPEICHEN	Sapim CX-Ray
REIFEN	CADEX GX, 700x40c, foldable, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIEDATEN

RAHMEN	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Sitzrohrlänge (mm)	390		420		465		500	
Sitzrohrwinkel	74.5°	74.4°	74.5°	74.4°	74.5°	74.4°	74.5°	74.4°
Oberrohrlänge (mm)	525	525	535	535	545	545	555	555
Steuerrohr-Länge (mm)	90		110		140		160	
Steuerrohr-Winkel	70.0°	69.9°	70.5°	70.4°	71.0°	70.9°	71.0°	70.9°
Gabelneigung (mm)	50		50		50		50	
Trail (mm)	78.4	82	75	78.5	71.6	75.1	71.6	75
Radstand (mm)	1012	1022	1019	1029	1026	1036	1043	1052
Kettenstreben-Länge (mm)	425	435	425	435	425	435	430	440
Tretlager-Höhe (mm)	80	81	80	81	80	81	80	81
Stack (mm)	523	524	544	545	574	575	593	594
Reach (mm)	380	379	384	383	386	385	391	389
Überstandshöhe (mm)	681	688	708	715	748	755	779	786
Lenkerbreite (mm)	400		400		420		420	
Vorbaulänge (mm)	50		60		70		80	
Kurbellänge (mm)	165		170		172.5		172.5	

Spezifikations-, Preis- und Farbänderungen vorbehalten.