

# DEVOTE ADVANCED PRO



## SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Ocean Twilight/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
VILICA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
LULA VOLANA	Giant Contact AeroLight, -10 degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
CIJEV SJEDALA	Giant D-Fuse SLR, composite, -5/+15mm offset
SJEDALO	Liv Approach SL
POGON	
RUČICE MJENJAČA	SRAM Force eTap AXS, 2x12
PREDNJI MJENJAČ	SRAM Force eTap AXS
STRAŽNJI MJENJAČ	SRAM Force eTap AXS
KOČNICE	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
RUČICE KOČNICA	SRAM Force eTap AXS hydraulic
KAZETA	SRAM Force, 12-speed, 10x36
LANAC	SRAM Force D2
POGON	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant CXR 1 Carbon Disc, [F] 35mm, [R] 35mm
NABE	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
ŽBICE	Sapim CX-Ray
GUME	CADEX GX, 700x40c, foldable, tubeless
DODACI	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

## GEOMETRIJA

OKVIR	XS	S	M
Dužina cijevi sjedala (mm)	SHORT   LONG	SHORT   LONG	SHORT   LONG
Kut cijevi sjedala	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Dužina gornje cijevi (mm)	525   525	535   535	545   545
Dužina prednje cijevi (mm)	90	110	140
Kut vilice	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°
Zakrivljenost vilice (offset) (mm)	50	50	50
Staza (mm)	78,4   82	75   78,5	71,6   75,1
Međuosovinski razmak kotača (mm)	1012   1022	1019   1029	1026   1036
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	425   435	425   435	425   435
Položaj osovine pogona (mm)	80   81	80   81	80   81
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	523   524	544   545	574   575
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	380   379	384   383	386   385
Prekoračna visina (mm)	681   688	708   715	748   755
Širina volana (mm)	400	400	420
Dužina lule volana (mm)	50	60	70
Dužina poluge pedale (mm)	165	170	172,5
Veličina kotača	700	700	700

Sve navedene specifikacije podložne su promjeni bez prethodne najave.