

DEVOTE ADVANCED PRO



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Nebula/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
VILICA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
LULA VOLANA	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
CIJEV SJEDALA	Giant D-Fuse SLR, composite, -5/+15mm offset
SJEDALO	Liv Grit SL
PEDALE	platform pedal [GCS, GTS], no pedal [All other GSC]
POGON	
RUČICE MJENJAČA	SRAM Force AXS E1, 2x12
PREDNJI MJENJAČ	SRAM Force AXS E1
STRAŽNJI MJENJAČ	SRAM Force AXS D2
KOČNICE	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
RUČICE KOČNICA	SRAM Force AXS E1 hydraulic
KAZETA	SRAM Force E1, 12-speed, 10x36
LANAC	SRAM Force E1
POGON	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant CXR 1, [F] 35mm, [R] 35mm
NABE	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
ŽBICE	Sapim CX-Ray
GUME	CADEX GX, 700x40c, foldable, tubeless
DODACI	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS		S		M	
	SHORT	LONG	SHORT	LONG	SHORT	LONG
Dužina cijevi sjedala (mm)	390		420		465	
Kut cijevi sjedala	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°
Dužina gornje cijevi (mm)	525	525	535	535	545	545
Dužina prednje cijevi (mm)	90		110		140	
Kut vilice	70,0°	69,9°	70,5°	70,4°	71,0°	70,9°
Zakrivljenost vilice (offset) (mm)	50		50		50	
Staza (mm)	78,4	82	75	78,5	71,6	75,5
Međuosovinski razmak kotača (mm)	1012	1022	1019	1029	1026	1036
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	425	435	425	435	425	435
Položaj osovine pogona (mm)	80	81	80	81	80	81
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	523	524	544	545	574	575
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	380	379	384	383	386	385
Prekoračna visina (mm)	681	688	708	715	748	755
Širina volana (mm)	400		400		420	
Dužina lule volana (mm)	50		60		70	
Dužina poluge pedale (mm)	165		170		172,5	

Sve navedene specifikacije podložne su promjeni bez prethodne najave.