

# DEVOTE ADVANCED PRO



## SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Carbon/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
VOORVORK	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELPEN	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
ZADEL	Liv Approach SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM Force eTap AXS, 2x12
VOORDERAILLEUR	SRAM Force eTap AXS Wide
ACHTERDERAILLEUR	SRAM Force eTap AXS
REMMEN	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x36
AANDRIJVING	SRAM Force D2
CRANKSET	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAVEN	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPAKEN	Sapim CX-Ray
BANDEN	CADEX AR, 700x40c, tubeless
EXTRA'S	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

Adviesprijs: € 6.999,00

## GEOMETRIE

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Zitbuis Lengte (mm)	390	420	465	500				
Zitbuis Hoek	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°				
Frame Lengte (horizontaal) (mm)	525   525	535   535	545   545	555   555				
Balhoofdbuis Lengte (mm)	90	110	140	160				
Balhoofdbuis Hoek	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°				
Vork Sprong (mm)	50	50	50	50				
Naloop (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75				
Wielbasis (mm)	1012   1022	1019   1029	1026   1036	1043   1052				
Liggende achtervork lengte (mm)	425   435	425   435	425   435	430   440				
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Stand Over Height (mm)	681   688	708   715	748   755	779   786				
Stuur breedte (mm)	400	400	420	420				
Stuurpen Lengte (mm)	50	60	70	80				
Cranklengte (mm)	165	170	172,5	172,5				
Wielmaat	700	700	700	700				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.