

DEVOTE ADVANCED PRO



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Ocean Twilight/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
VOORVORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact AeroLight, -10 degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELPEN	Giant D-Fuse SLR, composite, -5/+15mm offset
ZADEL	Liv Approach SL
AFMONTAGE	
SHIFTERS	SRAM Force eTap AXS, 2x12
VOORDERAILLEUR	SRAM Force eTap AXS
ACHTERDERAILLEUR	SRAM Force eTap AXS
REMMEN	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x36
AANDRIJVING	SRAM Force D2
CRANKSET	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR 1 Carbon Disc, [F] 35mm, [R] 35mm
NAVEN	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPAKEN	Sapim CX-Ray
BANDEN	CADEX GX, 700x40c, foldable, tubeless
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

Adviesprijs: € 6.699,00

GEOMETRIE

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Zitbuis lengte (mm)	390	420	420	465	500			
Zitbuis hoek	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°			
Frame Lengte (horizontaal) (mm)	525 525	535 535	545 545	555 555				
Balhoofdbuis Lengte (mm)	90	110	140	160				
Balhoofdbuis Hoek	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Vork Sprong (mm)	50	50	50	50				
Naloop (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Wielbasis (mm)	1012 1022	1019 1029	1026 1036	1043 1052				
Liggende achtervork lengte (mm)	425 435	425 435	425 435	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Stuur breedte (mm)	400	400	420	420				
Stuurpen Lengte (mm)	50	60	70	80				
Cranklengte (mm)	165	170	172,5	172,5				
Wielmaat	700	700	700	700				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.