

# DEVOTE ADVANCED PRO



## SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Nebula/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
VOORVORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELLEN	Giant D-Fuse SLR, composite, -5/+15mm offset
ZADEL	Liv Grit SL
PEDALEN	platform pedal [GCS, GTS], no pedal [All other GSC]
AFMONTAGE	
SHIFTERS	SRAM Force AXS E1, 2x12
VOORDERAILLEUR	SRAM Force AXS E1
ACHTERDERAILLEUR	SRAM Force AXS D2
REMMEN	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
REMHENDELS	SRAM Force AXS E1 hydraulic
CASSETTE	SRAM Force E1, 12-speed, 10x36
AANDRIJVING	SRAM Force E1
CRANKSET	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR 1, [F] 35mm, [R] 35mm
NAVEN	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPAKEN	Sapim CX-Ray
BANDEN	CADEX GX, 700x40c, foldable, tubeless
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Adviesprijs: € 6.699,00

## GEOMETRIE

FRAME	XS	S	M	L
Zitbuis lengte (mm)	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Zitbuis hoek	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Frame Lengte (horizontaal) (mm)	525   525	535   535	545   545	555   555
Balhoofdbuis Lengte (mm)	90	110	140	160
Balhoofdbuis Hoek	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Wielbasis (mm)	1012   1022	1019   1029	1026   1036	1043   1052
Liggende achtervork lengte (mm)	425   435	425   435	425   435	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81
Stack (mm)	523   524	544   545	574   575	593   594
Reach (mm)	380   379	384   383	386   385	391   389
Stand Over Height (mm)	681   688	708   715	748   755	779   786
Stuur breedte (mm)	400	400	420	420
Stuurpen Lengte (mm)	50	60	70	80
Cranklengte (mm)	165	170	172,5	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.