

DEVOTE ADVANCED PRO



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Chameleon Blue / Reflective Mushroom
RAMME	Advanced-Grade Composite
GAFFEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12x142mm thru-axle, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact SLR XR D-Fuse, 31.8, 5° back sweep, flare drop
STYRSTEM	Giant Contact, 8-degree
SETEPINNE	Giant D-Fuse SLR, composite
SADEL	Liv Alacra SL
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM Force eTap AXS
FRONTGIR	SRAM Force eTap AXS
BAKGIR	SRAM Force eTap AXS
BREMSE	SRAM Force eTap AXS hydraulic
BREMSEHENDLER	SRAM Force eTap AXS hydraulic
KASSETT	SRAM Force, 12-speed, 10x36
KJEDE	SRAM Force D1, 12-speed
KRANK	SRAM Force D1 DUB, 30/43
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant CXR-2 Carbon Disc WheelSystem
NAV	Giant CXR-2 Carbon Disc WheelSystem
EIKE	Giant CXR-2 Carbon Disc WheelSystem
DEKK	Maxxis Velocita, 700x40c, tubeless
EXTRAS	tubeless prepared

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	75,0°	75,0°	74,5°	74,5°
Top Tube Length (mm)	515	525	535	550
Head Tube Length (mm)	95	125	155	180
Head Tube Angle	70,5°	70,5°	71,0°	71,0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	75,9	75,9	72,5	72,5
Wheelbase (mm)	1013	1020	1022	1039
Chain Stay Length (mm)	430	430	430	430
Bottom Bracket Drop (mm)	80	80	80	80
Stack (mm)	530	558	588	612
StackToHandlebar (mm)	593	623	655	678
Reach (mm)	378	376	372	380
ReachToHandlebar (mm)	429	437	443	452
Stand Over Height (mm)	683	711	749	779
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	70	80	90	90
Crank Length (mm)	165	170	172,5	172,5
Wheel Size	700c	700c	700c	700c

Alle spesifikasjonene kan endres uten varsel.