

# DEVOTE ADVANCED PRO



## SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Nebula/Chrome
RAMME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
GAFFEL	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STYRSTEM	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SETEPINNE	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	Liv Grit SL
PEDALER	platform pedal [GCS, GTS], no pedal [All other GSC]
DRIVVERK	
GIRHENDLER	SRAM Force AXS E1, 2x12
FRONTGIR	SRAM Force AXS E1
BAKGIR	SRAM Force AXS D2
BREMSE	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
BREMSEHENDLER	SRAM Force AXS E1 hydraulic
KASSETT	SRAM Force E1, 12-speed, 10x36
KJEDE	SRAM Force E1
KRANK	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant CXR 1, [F] 35mm, [R] 35mm
NAV	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
EIKE	Sapim CX-Ray
DEKK	CADEX GX, 700x40c, foldable, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

## GEOMETRI

RAMME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°				
Top Tube Length (mm)	525   525	535   535	545   545	555   555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75				
Wheelbase (mm)	1012   1022	1019   1029	1026   1036	1043   1052				
Chain Stay Length (mm)	425   435	425   435	425   435	430   440				
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Stand Over Height (mm)	681   688	708   715	748   755	779   786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172,5	172,5				

Alle spesifikasjonene kan endres uten varsel.