

# DEVOTE ADVANCED PRO



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLORS</b>	Carbon/Chrome
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
<b>FORK</b>	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
<b>GRIPS</b>	Liv All Condition
<b>STEM</b>	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
<b>SEATPOST</b>	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
<b>SADDLE</b>	Liv Approach SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force eTap AXS, 2x12
<b>FRONT DERAILLEUR</b>	SRAM Force eTap AXS Wide
<b>REAR DERAILLEUR</b>	SRAM Force eTap AXS
<b>BRAKES</b>	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force eTap AXS hydraulic
<b>CASSETTE</b>	SRAM Force, 12-speed, 10x36
<b>CHAIN</b>	SRAM Force D2
<b>CRANKSET</b>	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
<b>HUBS</b>	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim CX-Ray
<b>TIRES</b>	CADEX AR, 700x40c, tubeless
<b>EXTRAS</b>	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

## GEOMETRY

FRAME	XS	S	M	L
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Top Tube Length (mm)	525   525	535   535	545   545	555   555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Wheelbase (mm)	1012   1022	1019   1029	1026   1036	1043   1052
Chain Stay Length (mm)	425   435	425   435	425   435	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81
Stack (mm)	523   524	544   545	574   575	593   594
Reach (mm)	380   379	384   383	386   385	391   389
Stand Over Height (mm)	681   688	708   715	748   755	779   786
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	50	60	70	80
Crank Length (mm)	165	170	172,5	172,5
Wheel Size	700	700	700	700

All specifications listed are subject to change without notice.