

# DEVOTE ADVANCED PRO



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLORS</b>	Nebula/Chrome
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
<b>FORK</b>	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
<b>GRIPS</b>	Liv All Condition
<b>STEM</b>	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
<b>SEATPOST</b>	Giant D-Fuse SLR, composite, -5/+15mm offset
<b>SADDLE</b>	Liv Grit SL
<b>PEDALS</b>	platform pedal [GCS, GTS], no pedal [All other GSC]
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force AXS E1, 2x12
<b>FRONT DERAILLEUR</b>	SRAM Force AXS E1
<b>REAR DERAILLEUR</b>	SRAM Force AXS D2
<b>BRAKES</b>	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force AXS E1 hydraulic
<b>CASSETTE</b>	SRAM Force E1, 12-speed, 10x36
<b>CHAIN</b>	SRAM Force E1
<b>CRANKSET</b>	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant CXR 1, [F] 35mm, [R] 35mm
<b>HUBS</b>	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim CX-Ray
<b>TIRES</b>	CADEX GX, 700x40c, foldable, tubeless
<b>EXTRAS</b>	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
<b>MAX TIRE CLEARANCE</b>	53mm

## GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°				
Top Tube Length (mm)	525   525	535   535	545   545	555   555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75				
Wheelbase (mm)	1012   1022	1019   1029	1026   1036	1043   1052				
Chain Stay Length (mm)	425   435	425   435	425   435	430   440				
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Stand Over Height (mm)	681   688	708   715	748   755	779   786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172,5	172,5				

All specifications listed are subject to change without notice.