



## ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, L
FARBY	Carbon/Chrome
RÁM	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
VIDLICA	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
TLMIČ	N/A
KOMPONENTY	
RIADIDLÁ	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPY	Liv All Condition
PREDSTAVEC	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEDLOVKA	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
SEADLO	Liv Approach SL
PEDÁLE	N/A
POHON	
RADENIE	SRAM Force eTap AXS, 2x12
PREŠMYKAČ	SRAM Force eTap AXS Wide
PREHADZOVAČKA	SRAM Force eTap AXS
BRZDY	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BRZDOVÉ PÁKY	SRAM Force eTap AXS hydraulic
KAZETA	SRAM Force, 12-speed, 10x36
REŤAZ	SRAM Force D2
KLUKY	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NÁBOJE	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
ŠPICE	Sapim CX-Ray
PNEUMATIKY	CADEX AR, 700x40c, tubeless
DOPLNKY	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

**Cena: 6 949 €**

## GEOMETRIA

RÁM	XS	S	M	L
	SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT
Dĺžka sedlovej trubky (mm)	390	420	465	500
Uhol sedlovej trubky	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Dĺžka hornej rámovej trubky (mm)	525   525	535   535	545   545	555   555
Dĺžka hlavovej trubky (mm)	90	110	140	160
Uhol hlavovej trubky	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Offset vidlice (mm)	50	50	50	50
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Rázvor (mm)	1012   1022	1019   1029	1026   1036	1043   1052
Dĺžka zadnej stavby (mm)	425   435	425   435	425   435	430   440
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80   81	80   81	80   81	80   81
Stack - výška riadenia (mm)	523   524	544   545	574   575	593   594
Reach (mm)	380   379	384   383	386   385	391   389
Výška rámu od zeme (mm)	681   688	708   715	748   755	779   786
Šírka riaditok (mm)	400	400	420	420
Dĺžka predstavca (mm)	50	60	70	80
Dĺžka klúku (mm)	165	170	172,5	172,5
Rozmer kolies	700	700	700	700

*Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.*