

DEVOTE ADVANCED PRO



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Carbon/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
VILICE	Advanced SL-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, composite XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
OPORA KRMILA	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
OPORA SEDEŽA	Giant Contact SLR D-Fuse, composite, -5/+15mm offset
SEDEŽ	Liv Approach SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM Force eTap AXS, 2x12
PREDNJI MENJALNIK	SRAM Force eTap AXS Wide
ZADNJI MENJALNIK	SRAM Force eTap AXS
ZAVORE	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Force eTap AXS hydraulic
VERIŽNIK	SRAM Force, 12-speed, 10x36
VERIGA	SRAM Force D2
GONILKE Z VERIŽNIKI	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
PESTA	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
NAPERE	Sapim CX-Ray
PLAŠČI	CADEX AR, 700x40c, tubeless
DODATKI	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Kot sedežne cevi	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Top Tube Length (mm)	525 525	535 535	545 545	555 555
Višina glave okvirja (mm)	90	110	140	160
Krmični kot	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Zamik vpetja osi (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Medosna razdalja (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Oddaljenost zgornje cevi od gonilne osi (mm)	523 524	544 545	574 575	593 594
Doseg (mm)	380 379	384 383	386 385	391 389
Višina zgornje cevi (mm)	681 688	708 715	748 755	779 786
Širina krmila (mm)	400	400	420	420
Dolžina opore krmila (mm)	50	60	70	80
Dolžina gonilke (mm)	165	170	172,5	172,5
Velikost obročnikov	700	700	700	700

Vse navedene specifikacije se lahko spremenijo brez obvestila.