

# DEVOTE ADVANCED PRO



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Ocean Twilight/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
VILICE	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
OPORA KRMILA	Giant Contact AeroLight, -10 degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
OPORA SEDEŽA	Giant D-Fuse SLR, composite, -5/+15mm offset
SEDEŽ	Liv Approach SL
POGON	
PRESTAVNE ROČICE	SRAM Force eTap AXS, 2x12
PREDNJI MENJALNIK	SRAM Force eTap AXS
ZADNJI MENJALNIK	SRAM Force eTap AXS
ZAVORE	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Force eTap AXS hydraulic
VERIŽNIK	SRAM Force, 12-speed, 10x36
VERIGA	SRAM Force D2
GONILKE Z VERIŽNIKI	SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant CXR 1 Carbon Disc, [F] 35mm, [R] 35mm
PESTA	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
NAPERE	Sapim CX-Ray
PLAŠČI	CADEX GX, 700x40c, foldable, tubeless
DODATKI	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

## GEOMETRIJA

OKVIR	XS	S	M	L
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Dolžina sedežne cevi (mm)	390	420	465	500
Kot sedežne cevi	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Top Tube Length (mm)	525   525	535   535	545   545	555   555
Višina glave okvirja (mm)	90	110	140	160
Krmični kot	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Zamik vpetja osi (mm)	50	50	50	50
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Medosna razdalja (mm)	1012   1022	1019   1029	1026   1036	1043   1052
Dolžina cevi ob verigi (mm)	425   435	425   435	425   435	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81
Oddaljenost zgornje cevi od gonilne osi (mm)	523   524	544   545	574   575	593   594
Doseg (mm)	380   379	384   383	386   385	391   389
Višina zgornje cevi (mm)	681   688	708   715	748   755	779   786
Širina krmila (mm)	400	400	420	420
Dolžina opore krmila (mm)	50	60	70	80
Dolžina gonilke (mm)	165	170	172,5	172,5
Velikost obročnikov	700	700	700	700

Vse navedene specifikacije se lahko spremenijo brez obvestila.