

DEVOTE ADVANCED PRO



SPECS

| RAM | |
|--------------|--|
| STORLEKAR | XS, S, M, L |
| FÄRGER | Ocean Twilight/Chrome |
| RAM | Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing |
| GAFFEL | Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings |
| BAKDÄMPARE | N/A |
| KOMPONENTER | |
| STYRE | Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| GREPPAR | Liv All Condition |
| STAM | Giant Contact AeroLight, -10 degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm |
| SADELSTOLPE | Giant D-Fuse SLR, composite, -5/+15mm offset |
| SADEL | Liv Approach SL |
| DRIVLINAN | |
| VÄXLAR | SRAM Force eTap AXS, 2x12 |
| FRAMVÄXEL | SRAM Force eTap AXS |
| BAKVÄXEL | SRAM Force eTap AXS |
| BROMSAR | SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm |
| BROMSSPAKAR | SRAM Force eTap AXS hydraulic |
| KASSETT | SRAM Force, 12-speed, 10x36 |
| KEDJA | SRAM Force D2 |
| VEVPARTI | SRAM Force D2 DUB, 30/43 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm |
| BROMSREGLAGE | SRAM DUB, press fit |

| HJUL | |
|-----------------|---|
| FÄLGAR | Giant CXR 1 Carbon Disc, [F] 35mm, [R] 35mm |
| NAV | [F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle |
| EKRAR | Sapim CX-Ray |
| DÄCK | CADEX GX, 700x40c, foldable, tubeless |
| EXTRAFUNKTIONER | 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag |

Price: 78 890,00 kr

GEOMETRY

| RAM | S | | M | | L | |
|-----------------------|-------|-------|-------|-------|-------|-------|
| | SHORT | LONG | SHORT | LONG | SHORT | LONG |
| Längd sadelrör (mm) | 420 | 465 | 465 | 500 | 500 | 500 |
| Vinkel sadelrör | 74,5° | 74,4° | 74,5° | 74,4° | 74,5° | 74,4° |
| Topprörets längd (mm) | 535 | 535 | 545 | 545 | 555 | 555 |
| Styrhuvud Längd (mm) | 110 | 110 | 140 | 160 | 160 | 160 |
| Vinkel styrhuvud | 70,5° | 70,4° | 71,0° | 70,9° | 71,0° | 70,9° |
| Gaffelvinkel (mm) | 50 | 50 | 50 | 50 | 50 | 50 |
| Spår (mm) | 75 | 78,5 | 71,6 | 75,1 | 71,6 | 75 |
| Hjulbas (mm) | 1019 | 1029 | 1026 | 1036 | 1043 | 1052 |
| Kedjestagslängd (mm) | 425 | 435 | 425 | 435 | 430 | 440 |
| Nedre fäste Drop (mm) | 80 | 81 | 80 | 81 | 80 | 81 |
| Stack (mm) | 544 | 545 | 574 | 575 | 593 | 594 |
| Reach (mm) | 384 | 383 | 386 | 385 | 391 | 389 |
| Stå över höjden (mm) | 708 | 715 | 748 | 755 | 779 | 786 |
| Styrets bredd (mm) | 400 | 400 | 420 | 420 | 420 | 420 |
| Stamlängd (mm) | 60 | 60 | 70 | 70 | 80 | 80 |
| Vevlängd (mm) | 170 | 170 | 172,5 | 172,5 | 172,5 | 172,5 |
| Hjulstorlek | 700 | 700 | 700 | 700 | 700 | 700 |

All specifications listed are subject to change without notice.