

DEVOTE ADVANCED PRO



SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Nebula/Chrome
RAM	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
GAFFEL	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Contact SLR XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GREPPAR	Liv All Condition
STAM	Giant Contact AeroLight, -10 degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SADELSTOLPE	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	Liv Grit SL
PEDALER	platform pedal [GCS, GTS], no pedal [All other GSC]
DRIVLINAN	
VÄXLAR	SRAM Force AXS E1, 2x12
FRAMVÄXEL	SRAM Force AXS E1
BAKVÄXEL	SRAM Force AXS D2
BROMSAR	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors, [F]160mm, [R]160mm
BROMSSPAKAR	SRAM Force AXS E1 hydraulic
KASSETT	SRAM Force E1, 12-speed, 10x36
KEDJA	SRAM Force E1
VEVPARTI	SRAM Force D2 DUB, 30/43, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant CXR 1, [F] 35mm, [R] 35mm
NAV	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
EKRAR	Sapim CX-Ray
DÄCK	CADEX GX, 700x40c, foldable, tubeless
EXTRAFUNKTIONER	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 80 990,00 kr

GEOMETRY

RAM	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Längd sadelrör (mm)	390	420	465	500
Vinkel sadelrör	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Topprörets längd (mm)	525 525	535 535	545 545	555 555
Styrhuvud Längd (mm)	90	110	140	160
Vinkel styrhuvud	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Gaffelvinkel (mm)	50	50	50	50
Spår (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Hjulbas (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Kedjestagslängd (mm)	425 435	425 435	425 435	430 440
Nedre fäste Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Stå över höjden (mm)	681 688	708 715	748 755	779 786
Styrets bredd (mm)	400	400	420	420
Stamlängd (mm)	50	60	70	80
Vevlängd (mm)	165	170	172,5	172,5

All specifications listed are subject to change without notice.