

DEVOTE ADVANCED SL 0



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Tahitian Pearl
RUNKO	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
HAARUKKA	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMONENTIT	
OHJAUSTANKO	Liv Contact SLR XR Integrated XS: 70x380/420mm, S: 70x380/420mm, M: 80x380/420mm, L: 100x400/440mm
GRIPIT	Liv Stratus Elite 3.0
OHJAINKANNATIN	Liv Contact SLR XR Integrated XS: 70mm, S: 70mm, M: 80mm, L: 100mm
SATULATOLPPA	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SATULA	CADEX Amp
VOIMANSIIRTO	
VAIHDEVIPU	SRAM RED XPLR AXS E1, 1x13
TAKAVAIHTAJA	SRAM RED XPLR AXS E1
JARRUT	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
JARRUKAHVAT	SRAM RED E1 hydraulic
RATASPAKKA	SRAM RED E1, 13-speed, 10x46
KETJUT	SRAM RED E1
KAMPISARJA	SRAM RED XPLR AXS with power meter, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NAVAT	[F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes
PINNAT	CADEX Super Aero Carbon Spoke
RENKAAT	CADEX GXR, 700x45c, tubeless
LISÄTIEDOT	tubeless prepared, computer mount, chain guide
RAJOITTEET	
MAX RENGASVARA	53mm max tire size
MAX KETJUN KOKO	54t max chainring size

Suositushinta: 10 629,00 €

GEOMETRIA

RUNKO	XS	S	M	L
Satulaputken pituus (mm)	390	420	465	500
Satulaputken kulma	75,0°	74,5°	74,5°	74,0°
Vaakaputken pituus (mm)	528	538	548	562
Emäputken pituus (mm)	90	100	120	130
Emäputken kulma	70,5°	71,0°	71,5°	72,0°
Haarukan offset (mm)	50	50	50	50
Trail-mitta (mm)	75	72	69	65
Akseliväli (mm)	1024	1025	1031	1036
Takahaarukan alaputken pituus (mm)	433	433	433	433
Keskiön pudotus (mm)	80	80	80	80
Stack-mitta (mm)	525	537	557	569
Reach-mitta (mm)	387	389	394	399
Standover-mitta (mm)	663	714	752	801
Ohjaustangon leveys (mm)	380	380	380	400
Ohjainkannattimen pituus (mm)	70	70	80	100
Kammen pituus (mm)	165	165	170	172,5
Rengaskoko	700C	700C	700C	700C

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.