

DEVOTE ADVANCED SL 0



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Tahitian Pearl
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORK	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SLR XR Integrated XS: 70x380/420mm, S: 70x380/420mm, M: 80x380/420mm, L: 100x400/440mm
GRIPS	Liv Stratus Elite 3.0
STEM	Liv Contact SLR XR Integrated XS: 70mm, S: 70mm, M: 80mm, L: 100mm
SEATPOST	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SADDLE	CADEX Amp
DRIVETRAIN	
SHIFTERS	SRAM RED XPLR AXS E1, 1x13
REAR DERAILLEUR	SRAM RED XPLR AXS E1
BRAKES	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM RED E1 hydraulic
CASSETTE	SRAM RED E1, 13-speed, 10x46
CHAIN	SRAM RED E1
CRANKSET	SRAM RED XPLR AXS with power meter, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
HUBS	[F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes
SPOKES	CADEX Super Aero Carbon Spoke
TIRES	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	53mm max tire size
MAX CHAINRING SIZE	54t max chainring size

Suggested Retail Price (CDN): \$15,999.00

FRAME GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	390	420	465
Seat Tube Angle	75.0°	74.5°	74.5°
Top Tube Length (mm)	528	538	548
Head Tube Length (mm)	90	100	120
Head Tube Angle	70.5°	71.0°	71.5°
Fork Rake (mm)	50	50	50
Trail (mm)	75	72	69
Wheelbase (mm)	1024	1025	1031
Chain Stay Length (mm)	433	433	433
Bottom Bracket Drop (mm)	80	80	80
Stack (mm)	525	537	557
Reach (mm)	387	389	394
Stand Over Height (mm)	663	714	752
Handlebar Width (mm)	380	380	380
Stem Length (mm)	70	70	80
Crank Length (mm)	165	165	170
Wheel Size	700C	700C	700C

All prices and specifications are subject to change without notice.