

# DEVOTE ADVANCED SL 0



## SPECIFICATIES

| FRAME            |                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------|
| MATEN            | XS, S, M, L                                                                                        |
| KLEUREN          | Tahitian Pearl                                                                                     |
| FRAME            | Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout                                 |
| VOORVORK         | Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc       |
| ONDERDELEN       |                                                                                                    |
| STUUR            | Liv Contact SLR XR Integrated XS: 70x380/420mm, S: 70x380/420mm, M: 80x380/420mm, L: 100x400/440mm |
| HANDVATTEN       | Liv Stratus Elite 3.0                                                                              |
| STUURPEN         | Liv Contact SLR XR Integrated XS: 70mm, S: 70mm, M: 80mm, L: 100mm                                 |
| ZADEL PEN        | Giant Contact SLR XR D-Fuse, composite, 20mm offset                                                |
| ZADEL            | CADEX Amp                                                                                          |
| AFMONTAGE        |                                                                                                    |
| SHIFTERS         | SRAM RED XPLR AXS E1, 1x13                                                                         |
| ACHTERDERAILLEUR | SRAM RED XPLR AXS E1                                                                               |
| REMMEN           | SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm                               |
| REMHENDELS       | SRAM RED E1 hydraulic                                                                              |
| CASSETTE         | SRAM RED E1, 13-speed, 10x46                                                                       |
| AANDRIJVING      | SRAM RED E1                                                                                        |
| CRANKSET         | SRAM RED XPLR AXS with power meter, 42t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm                  |
| BOTTOM BRACKET   | SRAM DUB, press fit                                                                                |

| WIELSET            |                                                                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| VELGEN             | CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm                                                                                              |
| NAVEN              | [F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes |
| SPAKEN             | CADEX Super Aero Carbon Spoke                                                                                                                               |
| BANDEN             | CADEX GXR, 700x45c, tubeless                                                                                                                                |
| EXTRA'S            | tubeless prepared, computer mount, chain guide                                                                                                              |
| LIMITS             |                                                                                                                                                             |
| MAX TIRE CLEARANCE | 53mm max tire size                                                                                                                                          |
| MAX CHAINRING SIZE | 54t max chainring size                                                                                                                                      |

Adviesprijs: € 9.999,00

## GEOMETRIE

| FRAME                           | XS    | S     | M     | L     |
|---------------------------------|-------|-------|-------|-------|
| Zitbuis lengte (mm)             | 390   | 420   | 465   | 500   |
| Zitbuis hoek                    | 75,0° | 74,5° | 74,5° | 74,0° |
| Frame Lengte (horizontaal) (mm) | 528   | 538   | 548   | 562   |
| Balhoofdbuis Lengte (mm)        | 90    | 100   | 120   | 130   |
| Balhoofdbuis Hoek               | 70,5° | 71,0° | 71,5° | 72,0° |
| Vork Sprong (mm)                | 50    | 50    | 50    | 50    |
| Naloop (mm)                     | 75    | 72    | 69    | 65    |
| Wielbasis (mm)                  | 1024  | 1025  | 1031  | 1036  |
| Liggende achtervork lengte (mm) | 433   | 433   | 433   | 433   |
| Bottom Bracket Drop (mm)        | 80    | 80    | 80    | 80    |
| Stack (mm)                      | 525   | 537   | 557   | 569   |
| Reach (mm)                      | 387   | 389   | 394   | 399   |
| Stand Over Height (mm)          | 663   | 714   | 752   | 801   |
| Stuur breedte (mm)              | 380   | 380   | 380   | 400   |
| Stuurpen Lengte (mm)            | 70    | 70    | 80    | 100   |
| Cranklengte (mm)                | 165   | 165   | 170   | 172,5 |
| Wielmaat                        | 700C  | 700C  | 700C  | 700C  |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.