DEVOTE ADVANCED SL 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Ember Violet
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORK	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SLR XR Integrated XS: 380/420mm, S: 380/420mm, M: 380/420mm, L: 400/440mm
GRIPS	Liv Stratus Elite 3.0
STEM	Liv Contact SLR XR Integrated XS: 60mm, S: 70mm, M: 80mm, L: 100mm
SEATPOST	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SADDLE	Liv Grit SLR
DRIVETRAIN	
SHIFTERS	SRAM Force XPLR AXS E1, 1x13
REAR DERAILLEUR	SRAM Force XPLR AXS E1
BRAKES	SRAM Force AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Force E1 hydraulic
CASSETTE	SRAM Force E1, 13-speed, 10x46
CHAIN	SRAM Force E1
CRANKSET	SRAM Force XPLR AXS with power meter, 40t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
HUBS	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
SPOKES	Aero Bladed Carbon Spoke
TYRES	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	53mm max tire size
MAX CHAINRING SIZE	54t max chainring size

Price: €8,399.00

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°
Top Tube Length (mm)	528	538	548	562
Head Tube Length (mm)	90	100	120	130
Head Tube Angle	70.5°	71.0°	71.5°	72.0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	75	72	69	65
Wheelbase (mm)	1024	1025	1031	1036
Chain Stay Length (mm)	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80
Stack (mm)	525	537	557	569
Reach (mm)	387	389	394	399
Stand Over Height (mm)	663	714	752	801
Handlebar Width (mm)	420	420	420	440
Stem Length (mm)	60	70	80	100
Crank Length (mm)	165	165	170	172.5
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.