DEVOTE ADVANCED SL 2



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Misty Aloe
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORGAFFEL	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYR	Liv Contact SLR XR Integrated XS: 380/420mm, S: 380/420mm, M: 380/420mm, L: 400/440mm
GREB / STYRBÅND	Liv Stratus Elite 3.0
FREMPIND	Liv Contact SLR XR Integrated XS: 60mm, S: 70mm, M: 80mm, L: 100mm
SADELPIND	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SADEL	Liv Grit SL
GEARGRUPPE	
SKIFTEGREB	SRAM Rival AXS E1, 1x13
BAGSKIFTER	SRAM Rival XPLR AXS E1
BREMSER	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BREMSEGREB	SRAM Rival E1 hydraulic
KASSETTE	SRAM Rival E1, 13-speed, 10x46
KÆDE	SRAM Rival E1
KRANKSÆT	SRAM Rival XPLR AXS with power meter, 40t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NAV	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
EGER	Aero Bladed Carbon Spoke
DÆK	CADEX GXR, 700x45c, tubeless
EKSTRA	tubeless prepared, computer mount, chain guide
GRÆNSER	
MAX DÆKSTØRRELSE	53mm max tire size
MAX KLINGE STØRRELSE	54t max chainring size

Pris: 51.609,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørslængde (mm)	390	420	465	500
Sadelrørsvinkel	75,0°	74,5°	74,5°	74,0°
Overrørslængde (mm)	528	538	548	562
Kronrørslængde (mm)	90	100	120	130
Kronrøsvinkel	70,5°	71,0°	71,5°	72,0°
Forgaffel fremspring (rake) (mm)	50	50	50	50
Sti (mm)	75	72	69	65
Akselafstand (mm)	1024	1025	1031	1036
Kædestagslængde (mm)	433	433	433	433
Krankboks drop (mm)	80	80	80	80
Stack (mm)	525	537	557	569
Reach (mm)	387	389	394	399
Skridthøjde (mm)	663	714	752	801
Styrbredde (mm)	420	420	420	440
Frempindslængde (mm)	60	70	80	100
Pedalarmslængde (mm)	165	165	170	172,5
Hjulstørrelse	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.