

DEVOTE ADVANCED SL 2



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Misty Aloe
CUADRO	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
TIJERA	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTES	
MANUBRIO	Liv Contact SLR XR Integrated XS: 70x380/420mm, S: 70x380/420mm, M: 80x380/420mm, L: 100x400/440mm
GRIPS	Liv Stratus Elite 3.0
POTENCIA	Liv Contact SLR XR Integrated XS: 60mm, S: 70mm, M: 80mm, L: 100mm
POSTE DE ASIENTO	Giant Contact SLR XR D-Fuse, composite, 20mm offset
ASIENTO	Liv Grit SL
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Rival AXS E1, 1x13
CAMBIO TRASERO	SRAM Rival XPLR AXS E1
FRENOS	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	SRAM Rival E1 hydraulic
CASSETTE	SRAM Rival E1, 13-speed, 10x46
CADENA	SRAM Rival E1
MULTIPLICACIÓN	SRAM Rival XPLR AXS with power meter, 40t XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
MAZAS	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
RAYOS	Aero Bladed Carbon Spoke
NEUMÁTICOS	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	53mm max tire size
MAX CHAINRING SIZE	54t max chainring size

Precio: \$122,990.00

GEOMETRÍA

CUADRO	XS	S	M	L
Longitud de la Base del Poste de Asiento (mm)	390	420	465	500
Ángulo de la Base del Poste de Asiento	75.0°	74.5°	74.5°	74.0°
Longitud del Tubo Superior (mm)	528	538	548	562
Longitud del Telescopio (mm)	90	100	120	130
Ángulo del Telescopio	70.5°	71.0°	71.5°	72.0°
Rake (mm)	50	50	50	50
Trail (mm)	75	72	69	65
Distancia entre Ejes (mm)	1024	1025	1031	1036
Longitud de Vaina Inferior (mm)	433	433	433	433
Caída del Eje de Centro (mm)	80	80	80	80
Stack (mm)	525	537	557	569
Reach (mm)	387	389	394	399
Altura del Tubo Superior al Suelo (mm)	663	714	752	801
Ancho del Manubrio (mm)	380	380	380	400
Longitud de la Potencia (mm)	60	70	80	100
Longitud de la Biela (mm)	165	165	170	172.5
Tamaño de las Ruedas	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.