

# DEVOTE ADVANCED SL FRAMESET



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Galaxy Nebula
<b>FRAME</b>	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
<b>FORK</b>	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Liv Contact SLR XR Integrated XS: 70x380/420mm, S: 70x380/420mm, M: 80x380/420mm, L: 90x400/440mm
<b>STEM</b>	Liv Contact SLR XR Integrated XS: 70mm, S: 70mm, M: 80mm, L: 90mm
<b>SEATPOST</b>	Giant Contact SLR XR D-Fuse, composite, 20mm offset

WHEELS	
<b>EXTRAS</b>	tubeless prepared, computer mount, chain guide
LIMITS	
<b>MAX TIRE CLEARANCE</b>	53mm max tire size
<b>MAX CHAINRING SIZE</b>	54t max chainring size

**Suggested Retail Price (CDN): \$5,899.00**

## FRAME GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°
Top Tube Length (mm)	528	538	548	562
Head Tube Length (mm)	90	100	120	130
Head Tube Angle	70.5°	71.0°	71.5°	72.0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	75	72	69	65
Wheelbase (mm)	1024	1025	1031	1036
Chain Stay Length (mm)	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80
Stack (mm)	525	537	557	569
Reach (mm)	387	389	394	399
Stand Over Height (mm)	663	714	752	801
Handlebar Width (mm)	380	380	380	400
Stem Length (mm)	70	70	80	100
Crank Length (mm)	165	165	170	172.5
Wheel Size	700C	700C	700C	700C

*All prices and specifications are subject to change without notice.*