DEVOTE ADVANCED SL FRAMESET



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Galaxy Nebula
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORK	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SLR XR Integrated XS: 70x380/420mm, S: 70x380/420mm, M: 80x380/420mm, L: 90x400/440mm
STEM	Liv Contact SLR XR Integrated XS: 70mm, S: 70mm, M: 80mm, L: 90mm
SEATPOST	Giant Contact SLR XR D-Fuse, composite, 20mm offset

WHEELS	
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	53mm max tire size
MAX CHAINRING SIZE	54t max chainring size

Price: €4,649.00

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°
Top Tube Length (mm)	528	538	548	562
Head Tube Length (mm)	90	100	120	130
Head Tube Angle	70.5°	71.0°	71.5°	72.0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	75	72	69	65
Wheelbase (mm)	1024	1025	1031	1036
Chain Stay Length (mm)	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80
Stack (mm)	525	537	557	569
Reach (mm)	387	389	394	399
Stand Over Height (mm)	663	714	752	801
Handlebar Width (mm)	420	420	420	440
Stem Length (mm)	60	70	80	100
Crank Length (mm)	165	165	170	172.5
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.