DEVOTE ADVANCED SL FRAMESET



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Galaxy Nebula
OKVIR	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
VILICE	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Liv Contact SLR XR Integrated XS: 70x380/420mm, S: 70x380/420mm, M: 80x380/420mm, L: 90x400/440mm
OPORA KRMILA	Liv Contact SLR XR Integrated XS: 70mm, S: 70mm, M: 80mm, L: 90mm
OPORA SEDEŽA	Giant Contact SLR XR D-Fuse, composite, 20mm offset

OBROČNIKI	
DODATKI	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	53mm max tire size
MAX CHAINRING SIZE	54t max chainring size

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	390	420	465	500
Kot sedežne cevi	75,0°	74,5°	74,5°	74,0°
Top Tube Length (mm)	528	538	548	562
Višina glave okvirja (mm)	90	100	120	130
Krmilni kot	70,5°	71,0°	71,5°	72,0°
Zamik vpetja osi (mm)	50	50	50	50
Trail (mm)	75	72	69	65
Medosna razdalja (mm)	1024	1025	1031	1036
Dolžina cevi ob verigi (mm)	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80
Oddaljenost zgornje cevi od gonilne osi (mm)	525	537	557	569
Doseg (mm)	387	389	394	399
Višina zgornje cevi (mm)	663	714	752	801
Širina krmila (mm)	420	420	420	440
Dolžina opore krmila (mm)	60	70	80	100
Dolžina gonilke (mm)	165	165	170	172,5
Velikost obročnikov	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.